

DCX3200



DCX3200

Features

- M-Card™ (Multi-stream CableCARD) Host support for conditional access
- OpenCable Application Platform (OCAP™) capable
- Compatible with Motorola DCT/DCH legacy software API set
- Single 1GHz digital video tuner (QAM 64/256)
- High-definition (HDTV) decode of MPEG-2, MPEG-4 AVC (H.264), VC-1
- Audio decode of Dolby® Digital, Dolby® Digital Plus, AAC-LC / HE-AAC, WMA9, MP3
- Optional MoCA™ home-networking interface
- Independent 1GHz DOCSIS tuner
- DOCSIS 2.0+ embedded Cable Modem with support for DSG and down-stream channel bonding (2 down, 1 up)
- SCTE 55-1 / SCTE 55-2 Out-of-band
- Video scaling (Picture-in-Graphics)
- Accelerated 2-D graphics
- 64 MB Flash (standard), 256 MB DRAM total (standard)
- Front Panel LED displays for Power, Data, and Record (MoCA™ only)
- Remote and On screen diagnostics
- Switched Digital Video Capable
- Macrovision®, HDCP, DTCP, and CGMS-A content protection schemes on the respective interfaces

As competition in the video service industry continues to increase, cable operators require advanced technologies for delivering a superior digital viewing experience and exciting new applications. Motorola has developed a sophisticated all-digital solution with the DCX series, the next generation of Host set tops. The DCX set-tops are loaded with features for improving bandwidth efficiency, providing high-definition video with surround sound audio, and bringing on-demand and interactive services to a connected home environment.

The Motorola DCX3200 is a High-definition set-top with a single 1 GHz tuner that supports both MPEG-2 and MPEG-4 AVC services. The all-digital DCX3200 includes the latest audio and video output interfaces, including HDMI™ and Dolby® Digital Plus audio. When configured with the optional MoCA™ home networking interface, the DCX3200-M can serve as a multimedia client for accessing content from other compatible devices in the home. An embedded DOCSIS 2.0+ cable modem provides support for DSG and downstream channel bonding.

Bandwidth Efficiency Solutions

The DCX3200 fully supports the growing consumer demand for high-definition programming and high bandwidth advanced applications. The DCX3200 provides new methods of efficiently utilizing limited bandwidth for delivering these services. For example, the DCX3200 is capable of decoding MPEG-4 video streams, requiring significantly less bandwidth than MPEG-2 to deliver comparable quality video services. The 1GHz digital video tuner in the DCX3200 supports future plant expansion, enabling operators to increase the number of available channels. The DCX3200 also supports Switched Digital Video (SDV) solutions, allowing service providers to maximize the use of their available bandwidth by delivering programming only to nodes where and when subscribers actively request that programming.

Home Networking

With the optional MoCA™ Home Networking component, the DCX3200-M provides the flexibility to not only watch your favorite programs on your schedule, but also choose the room in your home where you would like to view your programs. The DCX3200-M serves as a multimedia client that can access and playback recorded programs from a separate MoCA™-enabled DVR set-top within the home over the existing coaxial cabling.

Remote Diagnostic Capabilities

The DCX3200 supports Motorola's SmartStream Terminal Data Collector (STDC) service for remotely gathering important set top status and health information in a centralized server for evaluation and corrective action. STDC provides operators with the ability to isolate and troubleshoot plant issues, improve service quality, and reduce operation costs.